## FORTINO® Riviera

The compact windproof parasol





## Assortment

	Nominal size without flounce cm	Number of ribs	Order no. Frame anodised natural
$\bigcirc$	Ø 250	8 parts	311 00 250 171
$\cup$	Ø 300	8 parts	311 00 300 171
	200×200	8 parts	311 00 201 171
	240×240	8 parts	311 00 241 171


Nominal size	Lateral distance	Pole Ø	Area covered	Height closed	Clear headroom	Total height	Height open	Foundation	Minimum weight for base	max. wind speed open perm.
cm	cm	cm	m²	cm	cm	cm	cm	cm	kg	km/h (wind force)
A	AS	М	В	E	F	G	Н	С		
Ø 250	230	3.8	4.4	150	205	285	240	60×60	40	80 (9)
Ø 300	275	3.8	6.4	140	205	300	245	70×70	55	60 (7)
200×200	-	3.8	4.0	135	205	285	240	60×60	40	70 (8)
240×240	=	3.8	5.8	115	205	295	245	70×70	55	60 (7)


The listed measures represent extrapolated average values that may be slightly different on the product ( $\pm$  2 %  $\pm$  5 cm).


Height dimensions are based on ground socket BT. These vary slightly depending on the type of base. Except for steel base minus 5 cm.

 $The \ max. \ wind \ speed \ limits \ as \ per \ our \ separate \ list \ apply \ only \ in \ the \ presence \ of \ a \ fix \ ground \ anchorage. \ A \ base \ with \ the \ specified \ minimum \ weight \ is \ not \ sufficient.$ 

In the presence of several parasols, the minimum distance between one parasol and another and between parasols and walls shall be 20 cm.







Loose cover max. 10 cm, concrete thickness min. 30 cm (pay attention to frost depth), Guarantee water drainage



Accessories	Absolutely necessary	Order no.
Protective cover made of coated, tear-resistant polyester fabric		
1 Protective cover with zip and rod		350 01 609 980
10 pieces, protective cover with zip and rod		350 01 609 974
Electrical accessories		
2 OSYRION Spot LED battery-powered light, set of 2, with remote control, including charger		350 01 563 000
OSYRION Spot LED battery-powered light, set of 4, with remote control, including charger		350 01 563 100
Fixations		
Ground sockets		
4 Ground socket BT, hot-dip galvanised steel	Connection tube BT	350 01 206 100
Wall consoles  Wall bracket Z, 180 mm, hot-dip galvanised steel	Support tube Z	350 01 205 000
Bases Concrete base Z, 40 kg, Ø 60×8.5 cm, light concrete	Support tube Z	350 01 111 116
1 pallet (20 pieces) concrete base Z, 40 kg, Ø 60×8.5 cm, light concrete	Support tube Z Support tube Z	350 01 111 116
<sup>1</sup> Concrete base Z, 40 kg, Ø 60×8.5 cm	Support tube Z	350 01 112 110
Concrete base Z, 55 kg, Ø 60×11 cm, light concrete	Support tube Z	350 01 111 216
1 pallet (20 pieces) concrete base Z, 55 kg, Ø 60×11 cm, light concrete	Support tube Z	350 01 112 216
Natural granite base Z, 40 kg, 50 x 50 x 8 cm, natural stone.  Available from approx. March 2025. NEW	Support tube Z	350 01 109 467
Natural granite base Z, 55 kg, 59 x 59 x 8 cm, natural stone.  Available from approx. March 2025. NEW	Support tube Z	350 01 109 447
<sup>3</sup> Set of castors for natural granite base Z, 40/55/90 kg / M4, 120 kg, Ø 5 cm, galvanised steel NEW		350 01 109 487
3.8 Set of castors for natural granite base Z, 40/55/90 kg / M4, 120 kg, Ø 5 cm, high-grade steel 1.4301 / 304 NEW		350 01 109 486
Steel base Z 40 kg, 58.5 × 58.5 × 2 cm, hot-dip galvanised steel	Support tube Z	350 01 100 810
Steel base Z 55 kg, 68.5 × 68.5 × 2 cm, hot-dip galvanised steel	Support tube Z	350 01 100 910
0 <sup>3</sup> Set of castors for steel base Z, 40/55 kg, Ø 5 cm, galvanised steel Available from approx. february 2025. NEW		350 01 101 001
.0 <sup>3.8</sup> Set of castors for steel base Z, 40/55 kg, Ø 5 cm, high-grade steel 1.4301 / 304 NEW		350 01 101 000
Bases with castors		
.1 <sup>1.3</sup> Natural granite base Z, 40 kg, 45 × 45 × 8 cm, natural stone, with castors and retractable handle	Support tube Z	350 01 109 465
1 1.3 Natural granite base Z, 55 kg, 55 × 55 × 9 cm, natural stone, with castors and retractable handle	Support tube Z	350 01 109 445
2 <sup>3,7</sup> Base with castors Z, 55 kg, 65×65×11 cm, light concrete (without decorative plate)	Support tube Z + decorative plate	350 01 113 200
$^{3.7}$ 1 pallet (5 pieces) base with castors Z, 55 kg, 65 $\times$ 65 $\times$ 11 cm, light concrete (without decorative plate)	Support tube Z + decorative plate	350 01 113 280
3 Decorative plate in grey white RAL 9002 for base with castors Z, 55 kg, aluminium composite		350 01 113 310
4 Decorative plate in anthracite RAL 7016 for base with castors Z, 55 kg, aluminium composite		350 01 113 320
Various fixation types  5 Lawn spike Z, 85 × 150 × 350 mm, hot-dip galvanised steel	Support tube Z	350 01 205 400
Support tubes/Connection tubes		050.04.004.046
6 Support tube Z, Ø 35/38–39 mm, hot-dip galvanised steel		350 01 201 010
6 Support tube Z, Ø 35/38–39 mm, high-grade steel 1.4301/304		350 01 201 100
7 Connection tube BT, Ø 35/38–39 mm, hot-dip galvanised steel		350 01 206 210

¹ while stocks last

 $<sup>\</sup>ensuremath{^{\mathrm{3}}}$  only suitable for smooth, joint free surface coverings

<sup>&</sup>lt;sup>7</sup> 55 kg: Ground clearance 7 mm

<sup>&</sup>lt;sup>8</sup> suitable for corrosive environments

## FORTINO® Riviera







Frame 8 parts

Two-part profiled pole  $38.4 \times 2 \text{ mm}$ 

Opposite opening principle for easy opening

Quick and easy operation thanks to tensioning lever

Corrosion-resistant frame made of natural anodised aluminium with high-quality,

fibreglass-reinforced plastic parts, stainless-steel screws and rivets

Canopy self-tensing through flexible rib ends

Frame roof: round, square

Frame colour Aluminium, anodised

**Canopy** Fabric Quality 5: polyacrylic, 300 g/m², UV protection > 98 %

Fabric Quality 4: polyester, 250 g/m², UV protection > 98 % Fabric Quality 2: polyester, 220 g/m², UV protection > 98 %

Flounce Only available without

**Protective cover** Can be ordered as an optional extra

**Electrical accessories** Osyrion Spot LED with integrated battery pack







